INSTANT HAZE 1500 T G2

TOURING-HAZER WITH MICROPROCESSOR CONTROL

DESCRIPTION

Thanks to its robust tour case housing, the INSTANT HAZE 1500 G2 from Cameo's Instant Series is designed for tough touring use. With its maximum fluid consumption of only 9 ml per minute, extremely short warm-up time of less than a minute and ultra-silent operation, it is perfect for TV and film productions, fashion shows, live events and mobile discos.

The highly efficient micro-processor-controlled hazer features a durable evaporation tube made of austenitic stainless steel and automatic self-cleaning to prevent clogging and minimise maintenance. The vapour output can be regulated continuously without reheating and, like the fan speed, in 1% intervals for stages and rooms of any size.

The second generation of the INSTANT HAZE 1500 G2 has been optimised for even more comfortable handling: Thanks to the additional handle on the top, transporting and positioning the device is even easier. The modern touch display ensures particularly intuitive control directly on the device. In addition, the hazer now has a detachable powerCON TRUE1 connection for maximum flexibility and safety in the power supply.

The INSTANT HAZE 1500 G2 can be controlled in 2-channel mode via DMX and operated as a standalone unit. It is equipped with 3 and 5-pin DMX inputs and outputs and has a robust design with a slot for fluid canisters up to 5 litres. The device is protected against overheating.

For optimal results, use Cameo Instant Haze Fluid, which has been especially developed for Cameo Hazer. Use of other fluids will void the warranty and may damage the device.

FEATURES

- 1,500-watt touring hazer with microprocessor-controlled control unit
- Robust road case construction for demanding touring operations
- Additional handle on the top for easier transport and handling
- Intuitive touch display for particularly easy operation
- Detachable powerCON TRUE1 connection for flexible and secure power connection
- Durable stainless steel evaporation tube
- Automatic self-cleaning to prevent deposits
- Output and fan individually adjustable at 1 % levels
- 2-channel DMX control and stand-alone function
- Integrated slot for fluid canisters up to 5 l
- Ultra-silent operation – ideal for noise-sensitive applications
- Perfect for TV, film, fashion shows, live events and mobile discos
- Enhances the effect of any light show with a fine, long-lasting haze

SPECIFICATIONS

General	
Colour	Black

Control	
Controller protocols	DMX512, iDMX® (Transceiver)
Operating modes	DMX512
Number of DMX control modes	2
Stand alone operating modes	Stand-alone, Timer function
Data in connector	XLR 5-pole male, XLR 3-pole male
Data out connector	XLR 5-pole female, XLR 3-pole female

CLIH1500TG2

INSTANT HAZE 1500 T G2

TOURING-HAZER WITH MICROPROCESSOR CONTROL

Mains operation	
Operation voltage	230 V AC / 50 Hz
Rated power	1500 W
Inrush current	32 A / 0.03 ms @230 V (first half cycle)
Mains connector	Mains plug device outdoor male & TRUE1®
Mains fuse	F10AL/250 V
Fuse replacement	Possible from the outside without opening
Power out connector	Mains plug device outdoor female & TRUE1®

Housing	
Chassis material	Metal

Environmental	
Protection class	IP20
Ambient temperature	5 – 45 °C

Dimensions & weight	
Width	450 mm
Height	273 mm
Depth	585 mm
Weight	20.4 kg

Other properties	
Included Accessories	Mains cable

CLIH1500TG2